

LORENTZ S1-200 pump system

Description

The **LORENTZ S1-200** pump system is a portable and flexible system designed to pump water using solar power.

The system has an all plugged design for simple customer self installation. All equipment is rated for outdoor use. The system consists of a submersible helical rotor pump attached to a high efficiency brushless ECDRIVE motor. The system controller digitally controls the motor and monitors the system operation. Inputs are provided for connection of accessories for system automation (dry run protection and tank full sensor).

Features

- ★ High-efficiency ECDRIVE DC brushless motor and high efficiency helical rotor pump
- ★ System controller with plugged connections, integrated MPPT
- ★ Controller with Bluetooth® connectivity for local configuration and control
- ★ Simple S-Connect app for speed control, timers and extended trouble shooting

Technical data


Pump system	S1-200 HR-07	S1-200 HR-14	S1-200 HR-23
Max. flow rate	1 m ³ /h [4 US gpm]	1.9 m ³ /h [8 US gpm]	3 m ³ /h [13 US gpm]
Max. head	40 m [130 ft]	30 m [100 ft]	17 m [55 ft]

S1-200 controller data

Input (DC)	
Max. voltage (Voc)	55 V DC
Max. current (DC)	6 A
Max. PV short circuit current (Isc)	25 A
Output (DC)	
Max. voltage	55 V BLDC PWM 3-Phase
Max. frequency	170 Hz
Max. continuous current	6 A
Max. continuous power	250 W
Casing	
Enclosure	IP 68
Protective class	II
Sensor inputs	Dry run protection - Tank full switch
Casing material	Polycarbonate
General	
CONNECTED App	LORENTZ S-Connect
Ambient temperature	-40 ... +50 °C [-40 ... 122 °F]
Max. altitude rating	2,000 m [6,560 ft]
Environmental category	Outdoor
Pollution degree classification	PD3

S1-200 Controller dimensions and weights

W1	133.2 mm [5.2 in]
W2	150.0 mm [5.9 in]
W3	110.0 mm [4.3 in]
D1	43.0 mm [1.6 in]
D2	20.0 mm [0.8 in]
H1	151.7 mm [5.9 in]
H2	166.9 mm [6.5 in]
Net weight	0.3 kg [0.7 lb]



Pump end data

Pump type	HR - helical rotor
Pump outlet	26 mm [1.0 in] - hose push connection
Min. borehole diameter	100 mm [4 in]
Max. pump end efficiency	61 %
Rotor material	AISI 630
Stator material	polyphenylene sulfide

Water temperature range


Temp. class 2	+20 - +30 °C [68 - 86 °F]
Temp. class 3	+30 - +40 °C [86 - 104 °F]
Temp. class 4	+40 - +50 °C [104 - 122 °F]

Motor ECDRIVE data

Rated power	0.25 kW [0.3 HP]
Motor speed	750 ... 2,500 rpm
Insulation class	F
Enclosure class	IP 68
Max. motor efficiency	86 %
No. poles	8
Max. submersion	50 m [164 ft]
Motor material	polycarbonate
Length of cable	15 m [50 ft]
Cable size	3 x 2.1 mm ² - AWG 14
Cable plug	3-pin male


Pump with motor dimensions and weights

A	431.6 mm [16.9 in]
B	147.1 mm [5.7 in]
C	284.5 mm [11.2 in]
D	96.0 mm [3.7 in]
E	89.0 mm [3.5 in]
F	26.0 mm [1.0 in]
Pump end net weight	0.7 kg [1.5 lb]
Motor net weight	2.5 kg [5.5 lb]




Performance Range


S1-200 pump system HR-07



S1-200 pump system HR-14




S1-200 pump system HR-23



LORENTZ S-Connect App

With LORENTZ S-Connect App easily configure and control your S1-200 pumping system via Bluetooth® connectivity locally.

- ★ Download it for free on your Android™ smartphone from the Google Play Store
- ★ Connect to your pumping system and access multiple functions such as: Control and measurement of daily/weekly flow, speed, power, performance of connected sensors, timers setting, detailed troubleshooting scheme



Order and packaging information

Product name	Temp. class 2	Temp. class 3	Temp. class 4
S1-200 pump system HR-07	01-001020	01-001030	01-001040
S1-200 pump system HR-14	01-001070	01-001080	01-001090
S1-200 pump system HR-23	01-001120	01-001130	01-001140
Box content	1 x S1-200 controller		
	1 x pump with motor (with 15 m cable)		
	1 x PV adapter cable MC4		
	1 x hose clamp		
	2 x screws (controller PV mount)		
Packed gross weight	7.2 kg [15.4 lb]		
Packaging dimensions [LxWxH]	580 x 170 x 150 mm [23 x 6.7 x 5.9 in]		
Packed volume	0.015 m ³ [0.53 ft ³]		
Systems per pallet	54		

