

# Rolls



## FLOODED DEEP CYCLE BATTERY

**2 YS 31P**



Series	5000	Warranty	5 Years
Volts	2	BCI	SPEC
Cells	1	Plates/Cell	31
Terminal Type	Flag		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18		
Cables	19" 4/0 interconnect cables *RE incl.		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)
Float Voltage Range	2.25 V/cell @ 25°C (77°F)
Self-Discharge Rate	5%-10% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	5741
Marine Crank Amps (MCA) 32°F / 0°C	7176
Reserve Capacity (RC @ 25A)	6065 Minutes
Reserve Capacity (RC @ 75A)	2022 Minutes

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>3260 AH</b>	<b>32.60 A</b>
@ 72 Hour Rate	<b>3083 AH</b>	<b>42.82 A</b>
@ 50 Hour Rate	<b>2919 AH</b>	<b>58.38 A</b>
@ 20 Hour Rate	<b>2527 AH</b>	<b>126.36 A</b>
@ 15 Hour Rate	<b>2350 AH</b>	<b>156.69 A</b>
@ 10 Hour Rate	<b>2249 AH</b>	<b>224.92 A</b>
@ 8 Hour Rate	<b>2173 AH</b>	<b>271.67 A</b>
@ 5 Hour Rate	<b>2022 AH</b>	<b>404.35 A</b>
@ 1 Hour Rate	<b>1137 AH</b>	<b>1137.24 A</b>

Amphere hour capacity ratings based on specific gravity of 1.280. Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications



SAI GLOBAL  
ISO 9001  
Quality

Weight 129 kg 284.5 lbs

Length 39.4 cm 15.5"


Width 22.9 cm 9"

Height Inc. Term. 80.3 cm 31.63"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	95 mm	3.75"
Container (Inner)	Polypropylene	
Cover (Inner)	Polypropylene - heat sealed to inner container	
Container (Outer)	High Density Polyethylene	
Cover (Outer)	High Density Polyethylene snap fit to outer container	
Handles	Molded	

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

