



Series	AGM-R	Warranty	See Warranty Terms
Volts	12	BCI	4D
Cells	6		
Terminal Type	LT		
Included Hardware	Stainless Steel Nuts & Bolts		
Size & Thread	F10-M8		

### Charge

Recommended Charge Current Capacity (String)	40 A
Maximum Charge Current (String)	60 A
Self-Discharge Rate	Less than 2% per month at 25°C (77°F)

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	1100
Marine Crank Amps (MCA) 32°F / 0°C	1380
Reserve Capacity (RC @ 25A)	380 Minutes
Reserve Capacity (RC @ 75A)	100 Minutes

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	102%	100%	85%	65%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	<b>220 AH</b>	<b>2.2 A</b>
@ 20 Hour Rate	<b>200 AH</b>	<b>10 A</b>
@ 10 Hour Rate	<b>162 AH</b>	<b>16.2 A</b>
@ 5 Hour Rate	<b>144 AH</b>	<b>28.8 A</b>

Cut Off Voltage	Constant Current Discharge					
	1 hr	2 hr	3 hr	5 hr	8 hr	10 hr
VPC	103	55.1	40.8	28.8	19.6	16.2

### Specifications




Weight	55.5 kg	122.5 lbs
Length	52.2 cm	20.55"
Width	20.9 cm	8.23"
Height Inc. Term.	22.4 cm	8.82"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Container	ABS
Cover	ABS
Handles	Rope

### Cycle Life vs. Depth of Discharge



### Capacity vs. Temperature

