

SPECIFICATIONS

Relative Humidity Sensor

FEATURES

- Inexpensive, highly accurate relative humidity measurement
- High level voltage output signal
- Long term stability



The RH-5X is a low-cost continuous measurement relative humidity sensor. It is compatible with NRG Systems Symphonie loggers equipped with any iPack and RH SCM.

The RH-5X uses a polymer resistor sensor which provides excellent linearity and sensitivity with fast response time and long-term stability.

Sensor mounts to tower underneath shelter box via a bracket and hose clamp. Kit includes 1.5 m (5 feet) of cable, mounting bracket and hose clamp.

SPECIFICATIONS

Description	Sensor type	polymer resistor humidity sensor
	Applications	<ul style="list-style-type: none">• wind resource assessment• meteorological studies• environmental monitoring
	Sensor range	0 to 100% relative humidity
	Instrument compatibility	Symphonie with RH5 SCM & any Symphonie iPack
Output signal	Signal type	linear analog voltage
	Transfer function	% Relative Humidity = Voltage x 20
	Accuracy	+/- 3% RH from 20 to 80% RH [-20°C to 70°C (-4°F to 158°F)]
	Output signal range	0 to 5V for 0 to 100% RH, with a load resistance greater than 10 k ohms
Power requirements	Supply voltage	10 V to 36 V DC, 12 V at 2.6 mA typical
Installation	Mounting	Uses a sheet metal bracket with a hose clamp, to be mounted to the tower under the shelter box
	Tools required	8 mm (5/16 inch) nut driver or wrench



Global leaders in wind assessment technology

110 Riggs Road • Hinesburg • VT 05461 USA • TEL (802) 482-2255 • FAX (802) 482-2272 • EMAIL sales@nrgsystems.com

SPECIFICATIONS

Environmental	Operating temperature range	-40°C to 70°C (-40°F to 158°F)
	Operating humidity range	0 to 100% relative humidity
Physical	Connections	wire leads, 3 conductor shielded cable: <ul style="list-style-type: none">• Red: Power• Black: Ground• White: Signal out
	Cable length	1.5 m (5 feet)
	Weight	0.62 kg (1.36 pounds)
	Dimensions	110 mm (4.3 inches) x 109 mm (4.3 inches) x 50 mm (2.0 inches)
Materials	Cable	3 conductor 22 AWG, with overall foil shield and drain wire, chrome PVC jacket
	Enclosure	Polystyrene plastic box with galvanized steel mounting bracket

Global leaders in wind assessment technology



110 Riggs Road • Hinesburg • VT 05461 USA • TEL (802) 482-2255 • FAX (802) 482-2272 • EMAIL sales@nrgsystems.com