



EMPTY ENCLOSURE

# TK PC 1818-11-tm



## TK PC 1818-11-tm

Empty enclosure

**CUSTOMIZABLE**

182 x 180 x 111 mm  
Article number: 13750701

Empty enclosure - Industrial Quality -, base: glass fibre reinforced polycarbonate, grey, similar to RAL 7035, cover: polycarbonate, transparent

with metric knockouts



## Technical data

### Measures

Width:	182 mm
Length:	180 mm
Height:	111 mm
Inner height:	97 mm

### Material

Base:	Polycarbonate, glass-fibre reinforced, grey similar to RAL 7035
Cover:	Polycarbonate, transparent
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

### Other attributes

## Accessory

ASS-gro - External hinge set

HBA - Mounting material

MPS-KRI - Mounting plate

NS 35-144 - Mounting rail

TK ABL - External fixing lugs kit

TK MPI-1818 - Mounting plate



EMPTY ENCLOSURE

# TK PC 1818-11-tm

Ingress protection:	IP66 - acc. EN 60529 / DIN VDE 0470-1
---------------------	---

Impact resistance:	IK08 acc. DIN EN 5012 / VDE 0470 segment 100
--------------------	--

Protection class:	II - isolate protection acc. VDE 0106
-------------------	---

Rated insulation voltage AC:	690V V
------------------------------	--------

Rated insulation voltage DC:	1000 V
------------------------------	--------

Heavy metals-free:	Yes
--------------------	-----

PVC-free:	Yes
-----------	-----

Silicone-free:	Yes
----------------	-----

Combustion behaviour to UL:	V-2 acc. UL 94
-----------------------------	----------------

Combustion behaviour to VDE:	960°C acc. VDE 0471/ EN 60695
------------------------------	----------------------------------

Fitted for outdoor application:	Yes
---------------------------------	-----

sealable:	Yes
-----------	-----

Weatherproof:	Yes
---------------	-----

Knockouts:	Yes
------------	-----

## Environmental attributes

Ambient temperature (min.):	-35 °C
-----------------------------	--------

Ambient temperature (max.):	80 °C
-----------------------------	-------

Ambient temperature (24 h):	60 °C
-----------------------------	-------

Max. rel. humidity at 25° C (short Therm):	95%
---	-----

Max. rel. humidity at 40° C:	50%
------------------------------	-----